

ROUND VIBRATING SCREEN SERIES

YK

YK series vibrating screen is designed according to the mechanical principle of multi-layer number motion is circular motion, high efficiency new type of vibrating screen, and is designed for mine screening materials. At the same time, it is also widely used in the classification and screening of coal, building materials, electric power, chemical, railway, transportation, cement and other materials.

产品特点

Strong excitation force and high output

High screening efficiency and low vibration noise

The fuselage structure is novel, durable and easy to repair

产品参数

Model	Number of layers	Screen surface specifications mm	Maximum feed size mm	Processing power th	Vibration frequency(HZ)	Motor Power (kw)	Weight (kg)	Dimensions mm
F3YK-1200	3	1200*3000	100	7.5-80	16.2	7.5	3050	3300*1900*1500
F4YK-1648	4	1500*4800	200	30-250	13-16	18.5	7360	5900*2100*2150
F3YK-1854	3	1800*5400	250	50-300	16.2	22	8285	6500*2536*1910
F2YK-2160	2	2100*6000	250	100-400	16.2	30	9580	7150*2670*2120
F4YK-2160	4	2100*6000	250	100-400	16.2	37	11800	7150*2670*2650
F3YK-2460	3	2400*6000	300	150-600	16.2	30	12350	7150*2900*2350
F2YK-2475	2	2400*7500	300	200-650	16.2	22*2	12285	8491*3156*1613
F4YK-2475	4	2400*7500	300	200-650	16.2	23*2	15320	8491*3156*2713
F3YK-3072	3	3000*7200	350	200-800	16.2	30*2	15660	7991*3716*2163
F2YK-3680	2	3600*8000	350	300-1000	16.2	37*2	21560	8491*4556*1613
F4YK-3680	4	3600*8000	350	300-1000	16.2	37*2	25630	8491*4556*2163

Note: Specifications and models are subject to change without notice.